



High-resolution photospectral scanner Regula 88XX



Reading and authenticity verification of passports, ID cards, driver's licenses, visas and other security documents.

Capturing high-quality images at a resolution of 3401 ppi.

Reading RFID tags.



The device is designed as a single desktop unit. It has a set of light sources of visible, infrared and ultraviolet spectral ranges and imaging filters used for carrying out forensic expertise. The scanner enables to capture, process and store high-resolution document images. The reader is equipped with a module for reading RFID tags. Device operation is controlled via Regula High Resolution Scanner.

Functionality

- Capturing and processing images:
 - supported document formats:
 - ID-1
 - ID-2
 - ID-3
 - other documents with maximum size 190×142.5 mm (passport spread)
 - search and cropping of a document image from a general image
- The device enables examination of:
 - microprinting in white and IR light
 - security features (intaglio printing, laser engraving, etc.) in oblique IR and white light
 - OVD and holograms
 - security features in IR spectral ranges of 720, 870, 940 nm
 - security features (watermarks, microperforation, see-through register, etc.) in transmitted white and IR light 870 and 940 nm
 - $\circ\,$ security features in UV light 254 and 365 nm
 - retroreflective protection
 - IR luminescence
 - Anti-Stokes luminescence
- The MRZ detection and recognition
- Recognition and reading of 1D and 2D barcodes
- Automatic recognition of a document type
- Processing graphic fields
- OCR of the visual zone
- Reading RFID tags
- Analyzing and comparing text data
- Automatic authenticity verification of a document

Operation

- 1. The optical reader scans a document and captures document images in different illumination modes.
- 2. RFID tag data is read.
- 3. Regula Document Reader SDK processes the obtained data.
- 4. Verification results are ready for further use.

Application

- Border control services
- Aviation security services
- Law-enforcement agencies
- Immigration services
- Financial institutions
- Hotels
- Car rental and leasing companies
- Cellular companies
- Business centers security service
- Event-agencies
- Medical institutions
- Tourist agencies



- Ticket offices
- Visa support agencies and consulates
- Insurance companies
- Casino security service

Additional functions

• Multicolour LED indicator of the device status (red, green)

Delivery Set

- Regula Document Reader SDK
- USB cable for connecting the reader to a PC



Functionality			Model			
			8850F	8850M	8880	
Light sources	white	incident		+	+	+
		oblique (2 light	t sources)	+	+	+
		oblique for hole examination (4	ogram 15 light sources)	+	+	+
		coaxial		+	+	+
		transmitted		+	+	+
	ultraviolet, nm	254±10				+
		313±10				+
		365±10		+	+	+
	infrared, nm	incident	720±20	+	+	+
			870±20	+	+	+
			940±20		+	+
		oblique 870±2	0 (2 light sources)	+	+	+
		transmitted	870±20	+	+	+
			940±20		+	+
		high-intensity 800—1100	convertible		+	+
high-intensity incident cyan 505±20 nm			+	+		
Camera, Mp, not less			80	80	187	
Field of view, mm, maximum		190×142.5	190×142.5 and 135×101.5	190×127 and 135×90		
Resolution, ppi, not less			1386	1386 and 1952	2237 and 3401	
Reader of radio frequency identification devices (RFID)			+	+	+	

Reader of radio frequency identification devices (RFID)

- Frequency 13.56 MHz
- Supported standards ISO 14443: type A and B
- Data exchange rate, Kbaud 106, 212, 424, 848

Technical specifications

- Connection interface USB 3.0
- Power supply AC 100/240 V, 60/50 Hz, 5/2 A
- Weight, max, kg 40
- Overall dimensions (length×width×height), mm 540×480×480



Document reader software development kit (SDK)

SDK (Full) consists of three modules:

- Basic supplied together with a device by default
- VizOCR reading textual fields from a document page
- AAC automatic authenticity control

VizOCR and AAC modules are optional and used to extend the functionality of Basic module.

Updates for SDK are provided regularly. Basic module has unlimited support. VizOCR and AAC are updated on subscription basis.

	Functionality		Full SDK modules		
		Basi c(supplied by default)	VizOCR	AAC	
Doc	ument image capture and processing				
Document formats	 ID-1 (identity card) ID-2 (passport card, visa) ID-3 (passport) other document formats up to 190×140 mm 	+			
Scanning process	 search and cropping of a document image from a received image 	+			
	Machine readable zone (MRZ)				
Supported MRZ formats	 in conformity with ICAO 9303: 44×2 30×3 36×2 in conformity with ISO IEC 18013 (IDL): 30×1 support of special MRZ data structure for documents of certain countries 	+			
Features	 search for the MRZ along the whole document image MRZ recognition in infrared and white light control of check digits and data structure in conformity with the requirements of ICAO 9303 and BSI TR-03105 Part 5.1 evaluation of MRZ quality specifications in conformity with ICAO 9303, ISO 7501, 1831, 1073-2 standards 	+			
	Barcodes				
Supported formats	 1D: Codabar, Code39 (+extended), Code93, Code128, EAN-8, EAN-13, IATA 2 of 5 (Airline), Interleaved 2 of 5 (ITF), Matrix 2 of 5, STF (Industrial), UPC-A, UPC-E 2D: PDF417, Aztec Code, QR Code, Datamatrix 	+			
Authentication	barcode format check			+	
Automatic document type recognition					
Order of document type recognition	 Country→Type→Series 		+	+	
Features	 receiving a document template from the SDK database containing the following information: text and graphic fields position 		+	+	



			\sim	
	 availability of barcodes and security features authenticity verification and its parameters RFID-chip availability a reference image from Information Reference Systems «Passport», «Autodocs», «Frontline Documents System» processing of the received document images in compliance with the sample, including document image rotation by the angle given in the sample 			
	Graphic fields processing			
Types of graphic fields	 portrait of the document holder signature barcode fingerprint, etc. 	+		
Features	 cropping and displaying graphic fields as separate images in compliance with the sample of the corresponding document automatic searching of faces on the document image and cropping the document holder portrait if the document type is not recognized document image rotation according to the document holder portrait position 	+		
	OCR of the visual zone			
Recognition of character sets	 Central European and Eastern European Latin (1250) Cyrillic (1251) Western European Latin (1252) Greek (1253) Turkish (1254) Baltic (1257) other fonts of any size 		+	
Features	 dictionary support (name, surname, address, country, etc.) automatic text division into separate fields (e.g. dividing the address into postal code, country, state, etc.) recognition of dates with complex formats recognition of characters from different character sets in one line 		+	
	RFID SDK			
Supported RFID-chip standards	 ISO/IEC 14443-2 (type A and B) ISO/IEC 14443-3 (MIFARE® Classic Protocol) ISO/IEC 14443-4 	+		
Data access modes	 Direct BAC EAC PACE SAC 	+		
Authentication	 active (AA) passive (PA) chip (CA v1, CA v2) terminal (TA v1, TA v2) 	+		
Supported applications	 ePassport (DG1-DG16) eID (DG1-DG21) eSign 	+		



	• eDL (DG1-DG14)		
Certificate management	 local storage receiving certificates online through the program interface Master List, CRL support 	+	
Features	 reading RFID chips with extended length support reading RFID chips in compliance with ICAO LDS 1.7, PKI 1.1 data formats certified by BSI TR-03105 Part 5.1, BSI TR-03105 Part 5.2 	+	
Ar	nalysis and comparison of text data		
Document areas for cross-checking of the readout data	 MRZ VIZ RFID-chip barcode 	+	
Verification	 validity of any dates authenticity of names and surnames according to lists of wordstops zero numbers of sample documents 	+	
Adjustment of formats and measuring units to those used in the user OS	 date weight height, etc.	+	
Features	 complete or partial comparison of fields calculated field support (age, etc.) transliteration to Latin characters in compliance with ICAO 9303 standards for comparison with the MRZ 	+	
	Authenticity verification		
Operation available for any document	 checking luminescence (UV Dull Paper) of: the form the MRZ area the portrait area checking the MRZ print contrast in compliance with ICAO 9303 (IR B900 Ink) 		+
Operations available after document type recognition	 checking image patterns in white, IR and UV light checking luminescence of UV protection fibers detection of false luminescence checking photo embedding type: printing or attachment checking IR Visibility of: elements of the form text data the photograph (main and additional) detection of holograms (OVD), OVI reading a luminescent text and comparing it with the data obtained from the MRZ and VIZ (OCR Security Text) visualization of IPI (Invisible Personal Information) checking retroreflective protection checking barcode format 		+
Features	 checking operations are adjusted to documents with different degrees of wear and tear the choice of checking operations depends on security features available in a questioned document 		+



	Additional SDK functions		
Image formats	 .BMP .JPG .JP2 .PNG .TIF other image formats are possible on request 	+	
Interoperability	 comparison modules: fingerprint images from RFID chip and external fingerprint scanner face images from document data page and/or RFID chip Information Reference Systems «<u>Passport</u>», «<u>Autodocs</u>», «<u>Frontline Documents System</u>» 	*	
OS compatibility	• Windows 7 (x86, x64), Windows 8, Windows 10	+	
Drivers	Microsoft certified	+	
Features	 simultaneous optical scanning and RFID chip reading firmware upgrade via USB interface (automatic upgrade after installing new SDK version) multilingual interface 	+	
	Software updates		
SDK	twice a year	*	
Document template database	monthly	*	

* - on request / individual agreement



Estonian Passport, 2021



Incident white light (original size)



Oblique white light



Ultraviolet (365 nm) light



Ultraviolet (313 nm) light




Incident infrared (870 nm) light

20 Euro, 2015



Oblique infrared (870 nm) light




High-intensity convertible infrared (980 nm) light



Hologram examination



Incident white light (original size)





Transmitted white light



Incident infrared (870 nm) light



Ultraviolet (365 nm) light



Oblique infrared (870 nm) light



Ultraviolet (254 nm) light



Transmitted infrared (870 nm) light



High-intensity incident cyan (505 nm) light